

“Blue Steel” CXT3000 Enterprise-Grade CompletePBX Telephony System Data Sheet

The Blue Steel CXT3000 is a heavy-duty, stand-alone, pre-configured, out-of-the-box featuring Xorcom CompletePBX 5 management interface, hot swappable disk drives, and two built-in redundant power supplies supporting up to four Astribank units. The CXT3000

may be equipped with up to 32 analog ports, up to eight BRI ISDN ports, and up to 4 E1/T1 PRI, T1 CAS or E1 R2 ports in a single, 19" 2U chassis. Additional PSTN/analog phone ports can be provided by connecting up to 24 external [Astribank](#) units via the USB2 ports, for a total of up to 800 PSTN/analog phones ports, up to 1000 users and up to 550 concurrent calls.



[To see the different CXT3000 configurations on our Web site click here.](#)

Features

- Unlimited voicemail boxes, hunt groups, call center groups, and auto attendants (IVRs)
- Basic built-in call center with call recording, barge and whisper
- Hot-desking
- Sophisticated Classes of Service for enhanced security
- Emergency notification module
- Endpoint manager
- User-friendly Web interface
- Interface in different languages
- CDR (Call Details Record)
- TDM/SIP/IAX trunks
- Remote extensions
- Voicemail
- Voicemail to email
- Web access to voicemail
- Fax support
- Fax to email
- IVR menu system
- Ring groups
- Call queues
- Conference rooms
- Follow me
- Time-based routing
- Advanced dialing rules
- Music-on-hold
- Paging and intercom
- Admin status screen
- Package manager (for easy updates)
- Network settings tool

Software

| | |
|-----------------------------|--|
| Management Interface | CompletePBX 5 (64-bit) |
| Linux version | CentOS 7 |
| Framework | Asterisk 13 |
| Security | Intrusion protection software, firewall protection |

| | |
|---|--|
| TwinStar Plus™ (optional) | High availability solution for CompletePBX systems |
|---|--|

Hardware


| | |
|--|---|
| Processor | Intel i3 2120 (3.3GHz, 2 Cores, 3MB cache) |
| RAM | 4GB |
| Hard disk | 2 x hot swappable 250 GB SSD/ 500 GB SSD |
| RAID1 | Dual hard drive for increased system reliability |
| Fan | 3 redundant fans |
| Echo Cancellation Module | Voice enhancement & echo cancellation (optional) |
| USB | 2 external, USB 2.0 |
| I/O Ports | Input/Output ports for Asterisk peripheral device support (optional and model-specific) |
| Rapid PA™ | Public Address capability for FXS port(s) - (optional and model-specific) |

Telephony

| | |
|--|--|
| Maximum number of concurrent calls | 550 (SIP only); 480 (PRI + FXS) |
| Maximum number of built in analog ports | 32 (additional ports with external Astribank units) |
| Number of E1 / T1 ports | 4 (up to 120 concurrent PRI/R2/CAS calls) |
| Max. telephony modules supported internally | 4 (additional ports are supported by adding Astribanks) |
| Maximum number of telephony ports supported internally | 144 (4xE1 PRI/R2/CAS + 24 analog ports) |
| Supported Xorcom telephony modules | <ul style="list-style-type: none"> • 8 ports FXS • 8 port FXS + I/O ports • 8 ports FXO • 2 ports FXO, 6 ports FXS + I/O ports • 6 FXO ports, 2 FXS ports • Up to 4 ports PRI/R2/CAS • Up to 8 ports BRI ISDN |

Power

| | |
|--------------|--|
| Power supply | Two internal, redundant, hot-swappable units |
| Voltage | Switching, auto adjust 100/240 Volts, 50/60 Hz |

| | |
|-------------------------------|---|
| Power consumption | 230 Watts (maximum) |
| Built in grounding connection |  |

Network

| | |
|--------------------------|-----------------------|
| Ethernet port - standard | 10/100/1000 Mb/s (x2) |
|--------------------------|-----------------------|

Maintenance and Support

- LCD (Liquid Crystal Display) touch panel, supporting:
 - ◆ Status of active systems, including:
 - All configured IP addresses
 - TwinStar™ (dual-server redundancy)
 - Redundant Power Supply (when configured)
 - Blink ports (extensions, channels, XPD and SPAN)
 - Active calls
 - ◆ Maintenance issues, including:
 - Asterisk restart
 - DAHDI restart
 - Server reboot
 - Server power off
 - ◆ Settings, including:
 - Enable/disable DHCP
 - Manual IP configuration
- Monitor and keyboard support
- Internal backup & restore utility
- External [Rapid Recovery™](#) backup utility (provided on disk-on-key)
- [Rapid Tunneling™](#) utility providing secure remote access for product support purposes
- Internet updates

Environment

| | |
|---------------------|-----------------------------------|
| Storage temperature | -20° to 70° Celsius (-4° -158° F) |
| Working temperature | 0° to 40° Celsius (32° -104° F) |
| Humidity | 20%-95%, non-condensing |

Dimensions and Weight

| | |
|--------|---|
| Weight | 7 Kg 15.4 lbs May vary, depending on configuration |
|--------|---|

| | |
|-------------------|---|
| Size | 19" 2U industry standard rack-mountable chassis |
| Dimensions | 44 x 44 x 9 cm (17.3 x 17.3 x 3.5") |

Specifications may change without prior notice.