

## Product Change Announcement

Product Name: **IP-PBX (2000 & 3000 series)** Date: 11-Nov-14  
 PID: **C/XR2000; C/XR3000; C/XE2000; C/XE3000; CXT3000; C/TS3000; CXTS3000** Number of Pages: 1  
 First S/N: **X1069500**

### Changes

1. The motherboard in the CXT, C/XE and C/XR 3000 series has been upgraded.
2. The memory in the CXT, C/XE and C/XR 3000 series has been upgraded. One of the features of the new memory board is support for [ECC memory](#).
3. Intelligent Platform Management Interface (IPMI) has been added to the CXT, C/XE and C/XR 3000 series enabling remote monitoring and maintenance of the IP-PBX.
4. There are now two external USB ports in the CXT, C/XE and C/XR 3000 series, instead of four.
5. All chassis for the 2U units (CXT, C/XE and C/XR 3000 series as well as the C/XE and C/XR 2000 series) have been increased in depth by 3 centimeters to create a new standard size for all.

### Detailed Specification

The following new hardware specifications are relevant for the indicated product lines:

IP-PBX Model	Hardware Version	Memory		Motherboard	
		New	Previous	New	Previous
CXT3000 (Blue Steel) and CXTS3000	2.0.0	4GB DDR3 PC3-12800 1600MHz (ECC memory)	2G DDR3 1333MHz x 2pcs	MBD-X9SCL-F-B	S1200KP
XE3000/CXE3000 and C/TS3000	4.0.0	4GB DDR3 PC3-12800 1600MHz (ECC memory)	2G DDR3 1333MHz x 2pcs	MBD-X9SCL-F-B	S1200KP
XR3000/CXR3000	6.0.0	4GB DDR3 PC3-12800 1600MHz (ECC memory)	2G DDR3 1333MHz	MBD-X9SCL-F-B	S1200KP
XE2000/CXE2000 and C/TS2000	3.4.0	No change		No change	
XR2000/CXR2000	3.5.0	No change		No change	